

LIGHT WOOD | WOOD | 1"1/2 CONCRETE TOPPING, 5/8" T&G PLYWOOD, ACOUSTITECH LEAD 3.3, INSONOMAT (SOPREMA) | DOUBLE GLUED DOWN

Acoustic performance

AllC: 54 to 58

ASTC: 58 to 62

ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1"1/2 concrete topping, 5/8" T&G plywood, AcoustiTECH Lead 3.3, Insonomat (Soprema)



FLOOR TYPE

Wood

INSTALLATION TYPE

Double glued down

GLUE

Adhesive AD-532+, Adhesive AD-316, Adhesive AD-844 MS

***OTHER MEMBRANES AVAILABLE :**

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) (See assembly picture above).

CEILING TYPE

Resilient channels

NUMBER OF GYPSUM

2

**ACOUSTIT
ECH LEAD
3.3**



Plus de
détails

**ADHESIV
E
AD-532+**



Plus de
détails

**ADHESIV
E AD-316**



Plus de
détails

**ADHESIV
E AD-844
MS**



Plus de
détails

**INSONOM
AT
(SOPREM
A)**



Plus de
détails

