

LIGHT WOOD | WOOD | 1"1/2 CONCRETE TOPPING, 5/8" T&G PLYWOOD, ACOUSTITECH LEAD 3.3, ACOUSTIVIBE, INSONOMAT (SOPREMA) | DOUBLE GLUED DOWN

Acoustic performance

AllC: 57 to 61

ASTC: 58 to 62

ASSEMBLY DETAILS

STRUCTURE

Light wood

ASSEMBLY COMPONENTS

1"1/2 concrete topping, 5/8" T&G plywood, AcoustiTECH Lead 3.3, Acoustivibe, Insonomat (Soprema)

FLOOR TYPE

Wood

INSTALLATION TYPE

Double glued down

GLUE

Adhesive AD-532+, Adhesive AD-844 MS, Adhesive AD-316

CEILING TYPE

Acoustic insulator

NUMBER OF GYPSUM

2



***OTHER MEMBRANES AVAILABLE :**

The Insonomat membrane (Soprema) can be substituted with the Silentcrete membrane (Soprema) (See assembly picture above).

***OTHER CEILING ISOLATORS AVAILABLE:**

- RSIC-1
- RC-1 BOOST
- TECSOUND CLG 3900

**ACOUST
ITECH
LEAD
3.3**



Plus de
détails

**ADHESI
VE
AD-532
+**




Plus de
détails

**ADHESI
VE
AD-844
MS**



Plus de
détails

**ACOUST
IVIBE**



Plus de
détails

**ADHESI
VE
AD-316**



Plus de
détails

**INSONO
MAT
(SOPRE
MA)**



Plus de
détails

www.acousti-tech.com